

<b>EN 032</b>	<b>EN 055</b>	<b>EN 120</b>	
<b>Temperature Range</b>	<b>Ambient Temp + 5°C / 100°C</b>		
<b>Temperature Sensor</b>	<b>Fe-Const</b>		
<b>Control System</b>	<b>N-Prime™ Programmable Microprocessor</b>		
<b>Displays</b>	<b>LED Displays for temperature and time</b>		
<b>Temperature Set and Reading Sensitivity</b>	<b>0,1°C</b>		
<b>Temperature Variation* @37°C</b>	<b>≤ ±0,5°C</b>		
<b>Temperature Fluctuation* @37°C</b>	<b>±0,1°C</b>		
<b>Programmable Alarm Limits</b>	<b>±0,5°C/5°C</b>		
<b>Timer</b>	<b>1 minute – 99,9 hours + Hold Position</b>		
<b>Delayed Start Timer</b>	<b>1 minute – 99,9 hours</b>		
<b>Recording Time Interval on External Memory</b>	<b>10 or 30 second; 1,5,30,60 minutes</b>		
<b>Useful Volume, litres</b>	<b>32</b>	<b>55</b>	<b>120</b>
<b>Number of Shelves (Standard/ Max.)</b>	<b>2/6</b>	<b>2/7</b>	<b>2/10</b>
<b>Internal Material</b>	<b>Stainless Steel</b>		
<b>External Material</b>	<b>Electrostatic Powder Coated Steel Sheet</b>		
<b>Power Consumption</b>	<b>300 W</b>	<b>350 W</b>	<b>400 W</b>
<b>Power Supply</b>	<b>230 V, 50 Hz</b>		
<b>Internal Dimension (WxDxH) mm</b>	<b>330x300x335</b>	<b>420x370x365</b>	<b>500x480x500</b>
<b>External Dimension (WxDxH) mm</b>	<b>565x500x685</b>	<b>645x560x710</b>	<b>730x670x850</b>
<b>Packing Dimension (WxDxH) mm</b>	<b>670x600x920</b>	<b>720x650x930</b>	<b>800x750x1070</b>
<b>Net/Packed Weight Kg.</b>	<b>38/42</b>	<b>46/49</b>	<b>66/71</b>