

- · Pre-amplified pH electrode
- Easy manual one or two point calibration
- Automatic Temperature Compensation
- · Low battery indicator

HI 8314 is a handheld pH/mV/°C meter designed to be reliable and easy-to-use.

HI 8314 uses the HI 1217D pre-amplified pH electrode and internal temperature sensor.

Manual calibration is performed at one or two points by adjusting the trimmers on the front panel. This instrument is ideal for applications that require a custom calibration point. Manual calibration can be extremely useful in order to achieve better accuracy.

HANNA	1
PH CALIBRATION  Dip electrode in ph buffer, 68 or 7.01  Adjust the Offset trimmer to match pH value for current temperature	H11217
trimmer to match pH value for current temperature Offset 6.8 pH 7.01 p	
pH	
TEMP CAL OFFSET SLOPE	

SPECIFICATIONS		HI 8314	
Range	pН	0.00 to 14.00 pH	
	mV	±1999 mV	
	Temperature	0.0 to 100.0°C	
Resolution	pН	0.01 pH	
	mV	1 mV	
	Temperature	0.1°C	
Accuracy (@20°C)	pН	±0.01 pH	
	mV	±1 mV	
	Temperature	±0.4°C (excluding probe error)	
pH Calibration		manual, two point, through trimmers (offset $\pm 1~\text{pH}$ ; slope: 80 to 110%)	
Temperature Compensation		automatic, 0 to 70°C (32 to 158 °F)	
pH Electrode		HI 1217D PEI body, pre-amplified pH electrode with internal temperature sensor, DIN connector and 1 m cable (included)	
Input Impedance		10 <sup>12</sup> Ohm	
Battery Type / Life		9V / approximately 100 hours of continuous use	
Environment		0 to 50°C (32 to 122°F); RH max 100%	
Dimensions		$145 \times 80 \times 36 \text{ mm} (5.7 \times 3.1 \times 1.4")$	
Weight		230 g (8.1 oz.)	

## ORDERING INFORMATION

HI 8314 is supplied with HI 1217D pH electrode, HI 70004 pH 4.01 buffer solution sachet, HI 70007 pH 7.01 buffer solution sachet, HI 700661 electrode cleaning solution sachets (2), calibration screwdriver, battery, protective case and instructions.

## **ELECTRODES**

HI 1217D PEI body, preamplified pH electrode

with internal temperature sensor, DIN connector and 1 m (3.3') cable

HI 3618D Glass body, preamplified ORP electrode with platinum sensor, internal temporature sensor and

internal temperature sensor and BNC connector with 1 m (3.3') cable

## **SOLUTIONS**

HI 7004L pH 4.01 buffer solution, 500 mL pH 7.01 buffer solution, 500 mL pH 7010L pH 10.01 buffer solution, 500 mL pH 10.01 buffer s

## **ACCESSORIES**

HI 710015 Shockproof rubber boot, blue HI 710016 Shockproof rubber boot, orange

For a complete list of Solutions and Electrodes, see the end of this section.

